



## P-Series IP Phones

### Sangoma's 3rd Generation of Feature-Rich Desk Phones

#### Datasheet

Sangoma's line of P-Series phones is designed to deliver the features you need, at price points perfect for every type of user, and every type of business. All models: have color screens, have high definition voice, are headset-ready, provide plug-and-play deployment, and have built-in productivity applications including call log, contacts, user presence/status, parking and more. The P-Series phones are the only desk phones designed to be fully compatible across Sangoma's communications portfolio, further enhancing their value.\*



### P-Series

|   | P310 & P315 Value Models        | P320, P325, P330 Mid-Range Models | P370 Executive Model   | PM200 Expansion Module  |
|---|---------------------------------|-----------------------------------|--|-------------------------|
| Display   | 2.4" 320x240, Color             | 4.3" 480x272, Color, IPS          | 7.0" 800x1280, Color, IPS, Touch                             | 4.3" 272x480, Color, IP |
| Touchscreen   | No                              | No                                | Yes  | No                      |
| SIP Accounts  | 2                               | P320: 4; P325: 6<br>P330: 12      | 16<br>(using soft-keys)                                      | N/A                     |
| Programmable Keys (for Speed Dial/BLF or more SIP accounts) | 2                               | P320: 4<br>P325: 6<br>P330: 12    | 16<br>(using soft-keys)                                      | 2 rows of 10 keys       |
| Virtual Pages of Added Functionality                        | N/A                             | P320: N/A<br>P325: 20<br>P330: 10 | Up to 20 features/favorites on screen, with scrolling to 100 | 20 keys and 3 pages     |
| Ethernet LAN  | P310: 100 Mbps<br>P315: Gigabit | Gigabit                           | Gigabit  | N/A                     |
| Bluetooth and Built-in Wi-Fi (2.4/5G/802.11n)               | No                              | P320 & P325: No<br>P330: Yes      | Yes  | N/A                     |
| Expansion Module Support                                    | No                              | P320 & P325: No<br>P330: Yes      | Yes  | Yes                     |

\*Some apps require server-side support that may vary between platforms.

# Phone Specifications

## P310 & P315

### User Interface

- 2.4 in 320 x 240 px backlight color LCD
- 2 line appearance keys
- 4 feature keys
- 4 context-sensitive soft keys
- 6-key navigation controller
- 3-color LED msg waiting indicator
- Volume control

### Connections

- 4P4C (RJ-9) handset/headset jack
- 2 switched 10/100 Mbps Ethernet ports (P310)
- 2 switched 10/100/1000 Mbps Ethernet ports (P315)
- 12 volt 1.6A DC power port
- 2 lock ports
- Electronic hookswitch signaling port

### Box Dimensions

- 11.93" x 8.2" x 3.5", 2.4 lbs

### Software Minimum Version

- Switchvox >=7.7
- FreePBX & PBXact with Endpoint Manager

## P320, P325 & P330

### User Interface

- 4.3 inch, 480 x 272 pixel backlit color IPS LCD display
- SIP Accounts — P320: 4; P325: 6; P330: 12
- Rapid dial page scroll key for virtual keys: P320: no; P325/P330: yes
- 6 feature keys
- 4 context-sensitive soft keys
- 6-key navigation controller
- Backlit headset, speaker & mute keys
- 3-color LED message

### Connections

- 4P4C (RJ-9) handset/headset jack
- 2 switched 10/100/1000 Mbps Ethernet ports
- USB-A 2.0 ports: P320/P325: 1; P330: 2
- 12 volt 1.6A DC power port
- 2 lock ports
- Electronic hookswitch signaling port

### Box Dimensions

- 12.3" x 9.0" x 3.5", 3.0 lbs

### Software Minimum Version

- Switchvox >=7.9
- FreePBX & PBXact with Endpoint Manager

## P370

### User Interface

- 7.0 inch, 800 x 1280 pixel backlit color IPS LCD display
- Multi-point capacitive touch
- 16 line appearances (software)
- Feature and context-sensitive functions
- Dedicated touch control with backlight for Headset, Speaker, Mute, and without backlight for Volume functions
- 3-color LED message waiting indicator (MWI)

### Connections

- 4P4C (RJ-9) handset/headset jack
- 2 switched 10/100/1000 Mbps Ethernet ports
- 2 USB-A 2.0 ports
- 12 volt 1.6A DC power port
- 2 lock ports
- Electronic hookswitch signaling port

### Box Dimensions

- 11" x 9.0" x 3.5", 2.7 lbs

### Software Minimum Version

- Switchvox >=7.9
- FreePBX & PBXact with Endpoint Manager

# Series Specifications

## Phone Applications

- Visual Voicemail<sup>1</sup>
- Contacts
- Presence/Status
- Call Log
- Parked Calls
- Call Queues<sup>2</sup>
- Info
- Forward Calls
- Conference App<sup>2</sup>
- Hot Desking<sup>3</sup>

## Phone Features

- Auto-answer
- Headset-answer
- Headset-ring
- Distinctive ring
- Custom ringtones
- Call waiting
- Call transfer (unattended/attended)
- Call forward
- Call hold
- Call parking
- Call pickup
- Intercom/Paging

- Message Waiting Indication
- Busy Lamp Field (BLF)
- 3-way conferencing
- Do Not Disturb (DND)
- Redial
- Call timer
- Caller ID display

## Audio Support

- Handset, hands-free, and headset modes
- Full-duplex HD speakerphone with echo cancellation
- Hearing aid compatible
- Multicast audio playback
- Wideband: G.722
- Narrowband: G.711ulaw/alaw, G.726, G.729a

## Network Support

- Static or DHCP IP address assignment
- NTP time synchronization
- Priority queuing

- VLAN, LLDP, NAT traversal, QoS
- 802.1X pass-through
- 802.1X authentication
- OpenVPN Client

## Language Support

- Dutch, English, French, German, Italian, Spanish, Portuguese, Russian

## SIP/VoIP Support

- SIP v2
- TLS/SRTP
- DTMF, RFC4733
- SIP peer-to-peer
- SIP presence (SUBSCRIBE/NOTIFY)
- Per-account digit map/dial plan
- DialusingSIPURI
- Dial using SIP server
- Secure SIP authentication

## Provisioning

- CommUnity

- Switchvox Cloud & Prem
- Business Voice/Voice +
- FreePBX & PBXact Endpoint Manager
- DPMA Deskphone Module for Asterisk
- DHCP Option 66
- XML Configuration

## Management

- Firmware update via browser
- Factory restore via UI
- Remote logging via syslog

## Regulatory Comp.

- CE Mark
- FCC Part 15, Class B

## Max Power

- P310/P315: 2.5W
- P320/P325: 4.5W, 9.5W with USB
- P330: 8.2W, 5W per USB, 18.2W total

## Operating Conditions

### Temperature

- Temperature: +32 to 122F/0to50C

### Relative Humidity

- 5% to 95% non-condensing

### Storage Temp

- 4 to 160F / -20 to 70C

## Warranty

- One year

<sup>1</sup> Visual Voicemail not supported on P310/P315 models

<sup>2</sup> Call Queues and Conferencing not supported on all models

<sup>3</sup> Some features are UC platform specific; not all platforms support all phone features